













	Edge-banded Full E Depth Tegular		banded Partial pth Tegular	Standard Tegular		Lay-in		
Available for Ceilings: 15/16" [24 mm] Grid and 9/16" [14 mm] Grid		Available for Ceilings: 15/16" [24 mm] GRID AND 9/16" [14 mm] GRID		Available for Ceilings: 15/16" [24 mm] GRID AND 9/16" [14 mm] GRID		Available for Ceilings: 15/16" [24 mm] GRID AND 9/16" [14 mm] GRID		
Edge-banded		Edge-banded Side Slot		Edge-banded Side Spline				
Available for: Walls and Ceilings (Direct attach, z-clips,		Available for Ceilings: 15/16" [24 mm] Grid		Available for Walls: Accepts Black or Matching Wood Veneer		NOTES: 1) Heavy Duty Grid Mains to be on Maximum 2' Centers 2) These edge conditions apply to 3/4" [19 mm] Thick Panels only		
C-Hangers, Torsion Springs, etc.)				Spline Spacer				
	RULON INTERNA 2000 Ring Way St. Augustine, F	TIONAL PROJECT: _ 32092			ISSUE DATE:		DRAWN BY:	PROJECT NUMBER:
(904) 584-1400 info @ rulonco.co www.rulonco.cor		om Edge Conditio		ons Details	REVISION DATE: MAR/14/2019		CHECKED BY: TDA	DRAWING NUMBER: