ENDURE[™] PRODUCT SHEET

SYSTEM: ENDURE DIRECT ATTACH | STYLE: ED400

Endure[™] Direct Attach is a tough, long-lasting ceiling system designed for a variety of applications, from adverse exterior environments to decorative interiors and more.





Endure[™] Direct Atach 400 is a wood-alternative, metal-alternative, or solid color virtually maintenancefree extruded polymer system with tongue & groove edges and a flat back for direct attach applications. The 400 ceiling system cosists of extruded linear strips that are installed end-to-end with perimeter and expansion trims as required to create a continuous, monolithic appearance.

Endure[™] Direct Attach 400 is available in Endure[™].



DESIGN

Endure[™] Direct Attach 400 is manufactured by the extrusion of Endure[™], a proprietary engineered polymer blend, and is a tongue & groove ceiling or wall system. Strips install via staples or rivets attached to the back of the groove. Primary Access Panels can be coordinated with MEP locations and cut in-field.



ACOUSTICS

Endure[™] Direct Attach 400 is manufactured with tongue & groove edges to achieve a monolithic appearance and is considered acoustically transparent.



FIRE PERFORMANCE

Endure[™] Direct Attach 400 has been tested and meets **Class A** requirements as per ASTM E-84. Extrusions and carriers require no additional fire treatment.



SUSTAINABILITY

Endure[™] Direct Attach 400 contributes to sustainability initiatives like **WELL** and **LEEDv4** through Indoor Advantage Gold certification.



SEISMIC

Endure[™] Direct Attach 400 is is generally **exempt from seismic code requirements.** Local code should be consulted to determine additional seismic requirements.



RULON INTERNATIONAL

2000 RING WAY ST. AUGUSTINE, FL. 32092 PHONE: 904-584-1400 WEB: RULONCO.COM EMAIL: INFO@RULONCO.COM

PRODUCT DETAILS

Endure[™] Direct Attach is twin-walled to provide added structural strength, and to enhance thermal insulation. Standard widths/profiles are as follows:

SYSTEM	ED400
W (WIDTH)	4" (NOMINAL)
T (THICKNESS)	3/8"
L (LENGTH)	12'
B (BACK)	SMOOTH
E (EDGE)	SQUARE



